

Cannes panel products

Product No. 016

Structural Plywood BS EN 636

General Product Description

Product Description	BS EN636 replaced BS6566 in 1998. Phenol formaldehyde bonded hardwood plywood intended for use as a structural component in external, internal humid and internal dry conditions.
Areas of application	Intended for environments where it is exposed to moisture for extended period of time. It performs longer in humid and wet conditions. Hospital & School, fixtures is required to last for 10s of years.
Species	Tropical Hardwood, shorea/ dipterocarpus
Dimensions	T: 9, 12, 18, 25mm; W x L: 1220 x 2440mm
No. of ply	9mm: 5 ply, 12mm: 5 ply, 18mm: 7ply, 25mm: 11 ply;
Glue	WBP Water Boil Proof, Phenolic formaldehyde Bonding complies with EN 314- Class 3 Formaldehyde emission: less than 0.08mg/L
Grade	BS EN636
Weight	Approx. 550kg/cbm
Moisture contents	MC 8 - 12
Country of Origin	Malaysia
Manufacturing Standards	BS EN 636 (2003)
Manufacturer Compliance Statement	



Cannes Co, Ltd. 61-69 Ho Yeung Street, Tap Shek Kok Tuen Mun, NT
tel: +852 9763 7529, fax: +852 2441 2687